




LUMINES Lighting DULIO Linear LED Luminaire



DULIO
by **LUMINES**[®]
LIGHTING

LUMINES Lighting Linear LED Luminaire is dedicated mainly for indoor use. It is used as a main and decorative light source. Due to its minimalistic design, it allows for various interior arrangements.

Exact length of the luminaire [mm]	613
Fixture height [mm]	88,5
Fixture depth [mm]	43
Input voltage	220-240V AC
Total luminous flux [lm] / Useful luminous flux [lm] in a sphere (360)°	3980
Color temperature CCT [K]	3900
Color	Anodized silver



SET INCLUDES

LED luminaire	Aluminum
Light source	Samsung LED
Diffuser material	PMMA
Diffuser color	Milk
Set of suspensions	
Line	1250 mm x 1,2 mm
Line with a ball	100 mm
Cable lock	M4 9x29 nickel plated
Nipple	M10x1 nickel plated
Ceiling mounting bracket	15x15 M10x1 nickel


PARAMETERS

Symbol	LUM-DULIOS-60-4K
Index	26-0000-26
Weight with packaging [kg]	2,3
Power on mode [W]	38
Energy efficiency class	F
Standby power [W]	0
Power factor	0,95
Luminous efficiency [lm / W]	104,2
Peak light [cd / klm]	302,74
CRI Ra	>80
R9	11

Chromaticity Coordinates (x)	0,3857
Chromaticity Coordinates (y)	0,3820
Radiation angle (°)	2x96
Color uniformity in MacAdam ellipses	<4 degrees
Strobe Effect Indicator (SVM)	0,04
Flicker Index (Pst LM)	0,3
Lighting maintenance factor [%]	96
Dimmable	Not
IP	20
Lifespan L70B50	>54000
Guarantee	60 months



Power Factor PF ≥0,9	Voltage 220-240 V 50-60 Hz	Power 38 W	CRI Ra >80	IP protection IP20	Beam angle 100° / 100°	Lifespan 54 000 h	off on 25 000	60% 0,02 s	Starting time <0,02 s	Temperature range +60 °C -20	
-----------------------------------	---	-------------------------	-------------------------	------------------------------	-------------------------------------	-----------------------------	-------------------------	----------------------	---------------------------------------	---	--





How to install?



Scan the QR code to
see the instructional video




LUMINES Lighting DULIO Linear LED Luminaire



DULIO
by **LUMINES**[®]
LIGHTING

LUMINES Lighting Linear LED Luminaire is dedicated mainly for indoor use. It is used as a main and decorative light source. Due to its minimalistic design, it allows for various interior arrangements.

Exact length of the luminaire [mm]	1213
Fixture height [mm]	88,5
Fixture depth [mm]	43
Input voltage	220-240V AC
Total luminous flux [lm] / Useful luminous flux [lm] in a sphere (360)°	8200
Color temperature CCT [K]	3900
Color	Anodized silver



SET INCLUDES

LED luminaire	Aluminum
Light source	Samsung LED
Diffuser material	PMMA
Diffuser color	Milk
Set of suspensions	
Line	1250 mm x 1,2 mm
Line with a ball	100 mm
Cable lock	M4 9x29 nickel plated
Nipple	M10x1 nickel plated
Ceiling mounting bracket	15x15 M10x1 nickel


PARAMETERS

Symbol	LUM-DULIOS-120-4K
Index	26-0000-24
Weight with packaging [kg]	3,72
Power on mode [W]	76
Energy efficiency class	F
Standby power [W]	0
Power factor	0,98
Luminous efficiency [lm / W]	107,7
Peak light [cd / klm]	299,36
CRI Ra	>80
R9	11

Chromaticity Coordinates (x)	0,3857
Chromaticity Coordinates (y)	0,3820
Radiation angle (°)	2x96
Color uniformity in MacAdam ellipses	<4 degrees
Strobe Effect Indicator (SVM)	0,04
Flicker Index (Pst LM)	0,3
Lighting maintenance factor [%]	96
Dimmable	Not
IP	20
Lifespan L70B50	>54000
Guarantee	60 months



Power Factor PF $\geq 0,9$	Voltage 220-240 V 50-60 Hz	Power 76 W	CRI Ra >80	IP protection IP20	Beam angle 100° 100°	Lifespan 54 000 h	off on 25 000	60% 0,02 s	Starting time <math>0,02</math> s	Temperature range +60 °C -20	
---	---	-------------------------	-------------------------	------------------------------	-----------------------------------	-----------------------------	-------------------------	----------------------	--	---	--





How to install?



Scan the QR code to
see the instructional video




LUMINES Lighting DULIO Linear LED Luminaire



DULIO
by **LUMINES**[®]
LIGHTING

LUMINES Lighting Linear LED Luminaire is dedicated mainly for indoor use. It is used as a main and decorative light source. Due to its minimalistic design, it allows for various interior arrangements.

Exact length of the luminaire [mm]	1813
Fixture height [mm]	88,5
Fixture depth [mm]	43
Input voltage	220-240V AC
Total luminous flux [lm] / Useful luminous flux [lm] in a sphere (360)°	12500
Color temperature CCT [K]	3900
Color	Anodized silver


 **ENERG**⁺

LUMINES Lighting
LUM-DULIOS-180-4K

A
B
C
D
E
F
G

F

117
kWh/1000h



2019/2015

SET INCLUDES

LED luminaire	Aluminum
Light source	Samsung LED
Diffuser material	PMMA
Diffuser color	Milk
Set of suspensions	
Line	1250 mm x 1,2 mm
Line with a ball	100 mm
Cable lock	M4 9x29 nickel plated
Nipple	M10x1 nickel plated
Ceiling mounting bracket	15x15 M10x1 nickel


PARAMETERS

Symbol	LUM-DULIOS-180-4K
Index	26-0000-25
Weight with packaging [kg]	5,36
Power on mode [W]	116,5
Energy efficiency class	F
Standby power [W]	0
Power factor	0,97
Luminous efficiency [lm / W]	105,3
Peak light [cd / klm]	299,36
CRI Ra	>80
R9	11

Chromaticity Coordinates (x)	0,3857
Chromaticity Coordinates (y)	0,3820
Radiation angle (°)	2x96
Color uniformity in MacAdam ellipses	<4 degrees
Strobe Effect Indicator (SVM)	0,04
Flicker Index (Pst LM)	0,3
Lighting maintenance factor [%]	96
Dimmable	Not
IP	20
Lifespan L70B50	>54000
Guarantee	60 months



Power Factor PF ≥0,9	Voltage 220-240 V 50-60 Hz	Power 117 W	CRI Ra >80	IP protection IP20	Beam angle 100° / 100°	Lifespan 54 000 h	off on 25 000	60% 0,02 s	Starting time <0,02 s	Temperature range +60 °C / -20	
-----------------------------------	---	--------------------------	-------------------------	------------------------------	-------------------------------------	-----------------------------	-------------------------	----------------------	---------------------------------------	--	--



How to install?



Scan the QR code to
see the instructional video

